



ICI05 SERIES

WIDE INPUT VOLTAGE RANGE 5-6 WATTS DC-DC CONVERTER

FEATURES

- 2:1 WIDE INPUT VOLTAGES:9-18V,18-36V,36-72V
- 5-6 WATTS 24PIN DIL(1.25x0.8x0.4inches) PACKAGE
- EFFICIENCY TO 82%
- PI INPUT FILTER

GENERAL SPECIFICATIONS


- SWITCHING FREQUENCY : 100KHz TYP.
- OUTPUT RIPPLE & NOISE : 100mVp-p(20MHz B.W.)
- ISOLATION VOLTAGE : 500VDC
- ISOLATION RESISTANCE : 10⁹ ohms
- STORAGE TEMPERATURE RANGE : -40°C TO 100°C
- OPERATING TEMPERATURE RANGE : -25°C TO +71°C
- SHORT CIRCUIT PROTECTION : CONTINUOUS
- CASE MATERIAL : BLACK COATED COPPER WITH NON-CONDUCTIVE BASE



ELECTRICAL SPECIFICATIONS

- INPUT VOLTAGE RANGE : 12V nominal ...
9-18V
:24V nominal ...
18-36V
:48V nominal ...
36-72V
- OUTPUT VOLTAGE ACCURACY : ±2%
- LINE REGULATION : ±0.5%
- LOAD REGULATION(SINGLE) : ±0.5% (F.L. to 10% Load)
- LOAD REGULATION(DUAL) : ±1.0% (F.L. to 1 / 4 Load)
- EFFICIENCY : see table

PART NO.	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	INPUT CURRENT		EFFICIENCY (%)
				NO LOAD	FULL LOAD	
ICI05-12S03R	9-18VDC	3.3VDC	1000mA	7.5mA	405mA	68
ICI05-12S05R	9-18VDC	5VDC	1000mA	7.5mA	545mA	76
ICI05-12S12R	9-18VDC	12VDC	470mA	7.5mA	585mA	80
ICI05-12S15R	9-18VDC	15VDC	400mA	7.5mA	625mA	80
ICI05-12D05R	9-18VDC	±5VDC	±500mA	12 A	545mA	76
ICI05-12D12R	9-18VDC	±12VDC	±230mA	12 A	575mA	80
ICI05-12D15R	9-18VDC	±15VDC	±190mA	12 A	590mA	80
ICI05-24S03R	18-36VDC	3.3VDC	1000mA	5mA	195mA	70
ICI05-24S05R	18-36VDC	5VDC	1000mA	5mA	265mA	78
ICI05-24S12R	18-36VDC	12VDC	470mA	5mA	285mA	82
ICI05-24S15R	18-36VDC	15VDC	400mA	5mA	305mA	82
ICI05-24D05R	18-36VDC	±5VDC	±500mA	7.5mA	265mA	78
ICI05-24D12R	18-36VDC	±12VDC	±230mA	7.5mA	285mA	81
ICI05-24D15R	18-36VDC	±15VDC	±190mA	7.5mA	295mA	81
ICI05-48S03R	36-72VDC	3.3VDC	1000mA	2mA	98mA	70
ICI05-48S05R	36-72VDC	5VDC	1000mA	2mA	133mA	78
ICI05-48S12R	36-72VDC	12VDC	470mA	2mA	145mA	81
ICI05-48S15R	36-72VDC	15VDC	400mA	2mA	154mA	81
ICI05-48D05R	36-72VDC	±5VDC	±500mA	3mA	265mA	78
ICI05-48D12R	36-72VDC	±12VDC	±230mA	3mA	142mA	81



Dimensions: inches/mm

Unless otherwise specified, all tolerances are $\pm 0.005/\pm 0.13$

PIN	SINGLE	DUAL
2,3	-INPUT	-INPUT
9	NC	COMMON
11	NC	-OUTPUT
14	+OUTPUT	+OUTPUT
16	-OUTPUT	COMMON
22,23	+INPUT	+INPUT